



S2-2375AGM

2 VOLTS



WEIGHT:	146.00 kg	322 Lbs.
LENGTH:	490 mm	19 1/4 Inches
WIDTH:	349 mm	13 3/4 Inches
HEIGHT*:	382 mm	15 Inches
* including terminal		
CONTAINER:	ABS	
COVER:	ABS	
TERMINALS:	16 x M8	
HANDLES:	None	

CAPACITY **2200** AH

HOUR RATE:	SPECIFIC GRAVITY	CAPACITY / AMP HOUR	CURRENT / AMPS
@ 100 HOUR RATE	1.280	2375	23.75
@ 20 HOUR RATE	1.280	2200	110.00
@ 10 HOUR RATE	1.280	2020	202.00
@ 8 HOUR RATE	1.280	1960	245.00
@ 5 HOUR RATE	1.280	1835	367.00

AT 77°F / 25°C



SAI GLOBAL
ISO 9001
Quality

MAX CHARGE CURRENT:	200 A	
CHARGING constant voltage	CYCLE:	2.4V ~ 2.55V / 77°F / 25°C
	FLOAT:	2.22V ~ 2.24V / 77°F / 25°C

CAPACITY AFFECTED BY TEMPERATURE (20 HR RATE)

104°F / 40°C	102%
77°F / 25°C	100%
32°F / 0°C	85%
5°F / -15°C	65%

SELF-DISCHARGE 77°F / 25°C

CAPACITY AFTER 3 MONTHS	91%
CAPACITY AFTER 6 MONTHS	82%
CAPACITY AFTER 12 MONTHS	64%

CYCLE LIFE VS. DEPTH OF DISCHARGE

